



Lloyd's  
Register

## Type Approval Certificate

*This is to certify that Certificate No.05/00052(E1) for the undernoted products is extended and renumbered as shown.*

This certificate is issued to:

<b>PRODUCER</b>	F.A. Mourikis S.A.
<b>PLACE OF PRODUCTION</b>	Kalamaki, Korinthos 200 03 Greece
<b>DESCRIPTION</b>	Marine plywood constructed from Okoume and/or Sapelli, with or without decorative outer veneers bonded with melamine urea fromaldehyde (MUF) adhesive
<b>TYPE</b>	Mourikis Okoupanel Marine Mourikis Sapelli Panel Marine
<b>APPLICATION</b>	Marine, offshore and industrial use for the construction of pleasure craft, small craft and other constructions.
<b>SPECIFIED STANDARD</b>	<b>BS 1088:2003</b> <b>EN 13986:2004</b> <b>BS EN 310:1993</b> <b>BS EN 314-1:1993</b> <b>BS EN 314-2:1993</b> <b>BS EN 717-2:1995</b> <b>DIN68705:1981</b>
<b>RATIINGS</b>	Durability of Okoume (to BS 1088:2003): Non-durable
<b>Certificate No.</b>	<b>05/00052(E2)</b>
<b>Issue Date</b>	09 September 2014
<b>Expiry Date</b>	18 May 2015
<b>Sheet</b>	1 of 2

  
**M. Jogia**  
**Global Technology Centre**  
**Southampton**  
**Lloyd's Register EMEA**

*Mountbatten House, 1 Grosvenor Square, Southampton, SO15 2JU.*

Lloyd's Register EMEA  
Is a subsidiary of Lloyd's Register Group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



Panel thickness (mm):	3, 4, 5, 6, 7, 8, 10, 12, 14, 15, 18, 20, 22, 25, 30, 35, 40 & 45
Veneer thickness (mm):	1.1, 1.5, 2.2, & 3.0
Durability of Sapelli (to BS 1088:2003):	Moderately-durable
Panel thickness (mm):	3, 4, 5, 6, 9, 12, 15, 18, 20, 22& 25
Veneer thickness (mm):	1 & 1.5

**OTHER CONDITIONS**

**Irrespective of the durability of the outer veneer, the overall classification of the panel will be that of non-durable in the case of Okoume or mix Okoume and Sapelli, and moderately durable in the case of Sapelli**

*"This Certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid certificate."*

*The Design Appraisal Document No. 05/00052(E2) and its supplementary Type Approval Terms and Conditions form part of this Certificate.*

<b>Certificate No.</b>	<b>05/00052(E2)</b>
<b>Issue Date</b>	09 September 2014
<b>Expiry Date</b>	18 May 2015
<b>Sheet</b>	2 of 2

**M. Jogia**  
**Global Technology Centre**  
**Southampton**  
**Lloyd's Register EMEA**

*Mountbatten House, 1 Grosvenor Square, Southampton, SO15 2JU.*

Lloyd's Register EMEA  
Is a subsidiary of Lloyd's Register Group